

MODEL 2201

Fiber Optic Modem Chassis

The 2201 Rack Mount chassis houses 10 - 2240, 2262 and 2270 Fiber Optic Modems, in any combination. Two Power Supply Slots allow single AC or redundant AC power.

The 2201's Power Monitor Card monitors the health of the power supplies. The card has visual indicators of Power Supply status and provide audio and relay closure alarms on power supply or power source failure.



FEATURES:

- **Holds up to Ten 2200 Series Modems**
- **115 VAC and 230 VAC, Power Supply Options**
- **Redundant Power Supply Option**
- **Power Failure Monitor**
- **Up to 10 Hot-swappable 2200 Series Fiber Optic Modems per Chassis**
- **Audio, Visual, and Dry Contact Alarms**
- **19" Rack Mount**



World Headquarters

20600 Prairie Street

Chatsworth, CA 91311-6008

Phone (818) 718-6300 • Fax (818) 718-6312

E-mail: fiber@canoga.com

MODEL 2201

Fiber Optic Modem Chassis

Specifications

- **PHYSICAL**

Dimensions

Chassis 8.8"H x 19"W x 15.4"D
(222mm x 482mm x 390mm)

Weight

Chassis 7.7 lbs (3.5 kg)
AC Power Supply 9.0 lbs (4 kg)

- **OPERATING ENVIRONMENT**

0° to +50°C (32° to 122° F)
10% to 90% RH (non-condensing)

- **POWER**

AC Power Supply

115 VAC, 50/60 Hz, 250W Max.
230 VAC, 50/60 Hz, 250W Max

World Headquarters

20600 Prairie Street
Chatsworth, CA 91311-6008
Phone (818) 718-6300 • Fax (818) 718-6312
www.canoga.com



60500409